

Chesterton 1935

Food-Grade Compression Packing

Independently Certified EC 1935 Compliant Compression Packing

Compliance is made easier with Chesterton® 1935 food-grade compression packing. While EC 1935 requires that manufacturers declare compliance with the standard, it does not require independent testing for verification, and it can be difficult to ensure your suppliers are compliant. However, you can rest assured with Chesterton 1935, because an independent lab has certified that the product is safe for food and beverage sealing applications.

With Chesterton's reputation for quality you can also expect excellent reliability in your pumps, valves, mixers, and agitators.

Technical Data

Shaft Speed	6 m/s (1200 fpm)
Temperature Limit	230 °C (450 °F)
Chemical Resistance	pH 0 to 14
Applicable Standards	EC 1935/2004 ¹ , WRAS ² , USDA ³ requirements for minimal food contact, FDA ⁴ 21 CFR 178.3620(a) and 177.1550

¹ European regulation on food safety

² Water Regulation Advisory Scheme - UK Approval


³ United States Department of Agriculture - US Approval

⁴ Food and Drug Administration - US Approval



Applications

Pumps, valves, cookers, blenders, agitators, mixers, and any other rotating or reciprocating equipment.



- Suitable for use in virtually all food media below 230°C
- Made with a virgin PTFE and white oil lubricant
- Independently certified EC 1935 compliant

Available Sizes

Size mm	Packaged* ± 10% kg	Length* M	Item Number
4.8	0.91	34.14	362449
6.4	0.91	14.48	362450
6.4	2.27	36.2	362453
8	0.91	8.46	362454
8	2.27	21.14	362463
9.5	0.91	5.61	362464
9.5	2.27	14.02	362465
10	0.91	4.94	362466
10	2.27	12.34	362468
12.7	0.91	3.23	362470
12.7	2.27	17.22	362479
12.7	4.54	16.15	362480
14.3	2.27	6.25	362481
16	4.54	10.97	362482
19	4.54	7.62	362483
22.2	4.54	5.49	362484

* Weights and Lengths are given for informational purposes only. Weights and Lengths are not contractual.

Chesterton ISO certificates available on
www.chesterton.com/corporate/iso

Technical data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W. Chesterton Company disclaims all warranties express or implied, including warranties of merchantability and fitness for a particular purpose. Liability, if any, is limited to product replacement only. Any images contained herein are for general illustrative or aesthetic purposes only and are not intended to convey any instructional, safety, handling or usage information or advice respecting any product or equipment. Please refer to relevant Safety Data Sheets, Product Data Sheets, and/or Product Labels for safe use, storage, handling, and disposal of products, or consult with your local Chesterton sales representative.

© 2017 A.W. Chesterton Company.

® Registered trademark owned by A.W. Chesterton Company
in USA and other countries, unless otherwise noted.

Distributed by:



Area Tecnica Srl
Strada Banchette 3/1 - 10090 Rosta (TO)
Tel. (+39) 011 4035367 - Fax (+39) 011 4113564
info@areatecnica.it - www.areatecnica.it